

屋内照明器具特性

品番 (品名)	XFL326EY				
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m				
管理番号	K0126502(1)DB1				
BZ分類	BZ3/0.9/BZ2				

器具効率	71%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	71%																																																						
保守率	良 中 否	0.81	0.6	4.4	3.7	3.2	2.8	4.4	3.6	3.1	2.8	4.2	3.5	3.1	2.8	4.1	3.5	3.1	2.8	2.7																																			
		0.77	0.8	5.3	4.6	4.2	3.8	5.2	4.6	4.1	3.8	5.1	4.5	4.1	3.8	4.9	4.4	4.1	3.8	3.7																																			
			1.0	5.8	5.2	4.8	4.5	5.7	5.2	4.8	4.5	5.6	5.1	4.7	4.5	5.4	5.0	4.7	4.4	4.3																																			
		0.68	1.25	6.2	5.7	5.3	5.1	6.1	5.7	5.3	5.0	6.0	5.6	5.3	5.0	5.8	5.5	5.2	5.0	4.8																																			
下方投影面積	c m ²	1.5	6.5	6.0	5.7	5.4	6.4	6.0	5.7	5.4	6.2	5.9	5.6	5.3	6.1	5.8	5.5	5.3	5.2																																				
		2.0	6.8	6.5	6.2	5.9	6.7	6.4	6.1	5.9	6.5	6.3	6.0	5.8	6.4	6.1	5.9	5.8	5.6																																				
取付高さ	器具間隔最大限		2.5	7.0	6.7	6.5	6.2	6.9	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.6	6.4	6.2	6.1	5.9																																			
	横方向 (A)	縦方向 (B)	3.0	7.1	6.9	6.6	6.5	7.0	6.8	6.6	6.4	6.9	6.7	6.5	6.3	6.7	6.5	6.4	6.3	6.1																																			
1.5m	2.74m	2.1m	4.0	7.3	7.1	6.9	6.7	7.2	7.0	6.8	6.7	7.0	6.9	6.7	6.6	6.9	6.7	6.6	6.5	6.3																																			
2	3.66	2.66	5.0	7.4	7.2	7.1	6.9	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.8	7.0	6.8	6.8	6.7	6.5																																			
2.5	4.57	3.22	7.0	7.5	7.4	7.2	7.1	7.4	7.3	7.2	7.1	7.2	7.1	7.0	7.0	7.1	7.0	6.9	6.8	6.7																																			
3	5.49	3.8	10.0	7.5	7.5	7.4	7.3	7.5	7.4	7.3	7.2	7.3	7.2	7.2	7.1	7.1	7.1	7.0	7.0	6.8																																			

