

屋内照明器具特性	
品番 (品名)	XFL326PS
光源	LDL40S.N/14/26(2600A) ×2      2600.0lm
管理番号	K0126768(4)DR1
BZ分類	BZ3/4.5/BZ4

器具効率	78%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	78%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.77 中 0.72 否 0.68	0.6	49	40	35	31	48	40	35	31	46	39	34	31	45	38	34	31	29	
		0.8	57	49	44	40	56	48	43	40	54	47	43	39	52	46	42	39	38	
		1.0	62	55	49	46	61	54	49	45	59	53	49	45	57	52	48	45	43	
		1.25	66	60	55	51	65	59	54	51	63	58	54	51	61	57	53	50	49	
下方投影面積	c m <sup>2</sup>	1.5	69	63	59	55	68	62	58	55	66	61	57	54	64	60	57	54	52	
		2.0	73	68	64	61	71	67	63	60	69	66	62	60	67	64	61	59	57	
取付高さ	器具間隔最大限		2.5	75	71	67	64	74	70	67	64	72	68	66	63	70	67	65	63	
	横方向 (A)	縦方向 (B)	3.0	77	73	70	67	75	72	69	67	73	71	68	66	71	69	67	65	63
1.5m	1.82m	2.11m	4.0	79	76	73	71	77	75	73	70	75	73	71	69	73	72	70	68	66
2	2.41	2.67	5.0	80	77	75	73	79	77	75	73	77	75	73	72	75	73	72	71	69
2.5	3	3.24	7.0	81	79	78	76	80	79	77	76	78	77	76	74	76	75	74	73	71
3	3.59	3.83	10.0	82	81	80	79	81	80	79	78	79	78	77	77	77	76	75	73	73

