

屋内照明器具特性

品番 (品名)	XL574PKVK	
光源	XL574PKV ×1	4770.0 lm
管理番号	K0130717(0)DB1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	0%	床	10%				10%				10%				10%				0%				
下方光束	100%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	57	45	37	32	56	44	37	32	53	43	36	31	51	42	36	31	29			
	中	0.77	0.8	67	56	48	42	66	55	48	42	63	54	47	42	60	52	46	42	40			
	否	0.68	1.0	74	63	56	50	72	62	55	50	69	61	54	49	67	59	54	49	47			
			1.25	80	70	63	57	78	69	63	57	75	68	62	57	72	66	61	56	54			
下方投影面積	cm ²		1.5	84	75	68	63	82	74	68	63	79	72	67	62	76	71	66	62	59			
	等価発光面積		2.0	90	82	76	71	88	81	76	71	85	79	74	70	82	77	73	70	67			
取付高さ	器具間隔最大限		2.5	93	87	82	77	91	86	81	77	88	84	79	76	86	82	78	75	72			
	横方向 (A)	縦方向 (B)	3.0	95	90	85	81	94	89	85	81	91	87	83	80	88	85	82	79	76			
1.5m	1.93m	1.92m	4.0	99	94	91	87	97	93	90	87	94	91	88	85	92	89	86	84	81			
2	2.56	2.56	5.0	100	97	94	91	99	96	93	90	96	94	91	89	94	91	89	87	85			
2.5	3.18	3.18	7.0	103	100	98	95	101	99	97	95	99	97	95	93	96	94	93	91	89			
3	3.82	3.81	10.0	104	102	101	99	103	101	100	98	100	99	98	96	98	97	96	94	92			

