

屋内照明器具特性

品番 (品名)	XLF443UNNJ (J YOUJ I)															
光源	LED5000_85_2500 x1 2500.0 1m															
管理番号	K0153354 (4) DB 1															
BZ分類	BZ10															

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 49%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	51%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																ZCM			
保守率	良 0.83	0.6	42	29	21	15	38	27	19	14	31	22	16	11	24	17	12	8	3	
	中 0.81	0.8	50	37	28	22	46	34	26	20	37	28	21	16	29	22	17	13	6	
	否 0.77	1.0	56	44	34	28	51	40	32	25	41	33	26	21	33	26	20	16	8	
下方投影面積	c m ²	1.25	62	50	41	34	56	45	37	31	46	37	31	26	36	30	24	20	11	
		1.5	66	55	46	39	60	50	42	36	49	41	35	30	39	33	28	24	14	
等価発光面積	c m ²	2.0	72	62	54	47	66	57	49	43	54	47	41	36	43	38	33	29	18	
		2.5	76	67	59	53	69	61	55	49	57	51	46	41	46	41	37	33	21	
取付高さ	器具間隔最大限		3.0	78	70	64	57	72	65	59	53	60	54	49	45	48	44	40	37	24
	横方向 (A)	縦方向 (B)																		
1.5m	0	0	4.0	82	75	70	64	76	70	64	59	63	59	54	50	52	48	45	41	28
2	0	0	5.0	85	79	74	69	78	73	68	64	66	62	58	54	54	51	48	45	30
2.5	0	0	7.0	88	83	79	75	81	77	73	70	69	65	62	59	57	54	52	49	34
3	0	0	10.0	90	87	83	80	84	80	77	74	71	68	66	64	59	57	55	53	38

