

屋内照明器具特性	
品番 (品名)	XFL326EY
光源	LDL40S.N/14/26(2600A) ×2 2600.0 1m
管理番号	K0126502(1)DB1
BZ分類	BZ3/0.9/BZ2

器具効率	71%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	71%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	4.4	3.7	3.2	2.8	4.4	3.6	3.1	2.8	4.2	3.5	3.1	2.8	4.1	3.5	3.1	2.8	2.7
	中	0.77	0.8	5.3	4.6	4.2	3.8	5.2	4.6	4.1	3.8	5.1	4.5	4.1	3.8	4.9	4.4	4.1	3.8	3.7
	否	0.68	1.0	5.8	5.2	4.8	4.5	5.7	5.2	4.8	4.5	5.6	5.1	4.7	4.5	5.4	5.0	4.7	4.4	4.3
			1.25	6.2	5.7	5.3	5.1	6.1	5.7	5.3	5.0	6.0	5.6	5.3	5.0	5.8	5.5	5.2	5.0	4.8
下方投影面積		cm ²	1.5	6.5	6.0	5.7	5.4	6.4	6.0	5.7	5.4	6.2	5.9	5.6	5.3	6.1	5.8	5.5	5.3	5.2
等価発光面積		cm ²	2.0	6.8	6.5	6.2	5.9	6.7	6.4	6.1	5.9	6.5	6.3	6.0	5.8	6.4	6.1	5.9	5.8	5.6
取付高さ	器具間隔最大限		2.5	7.0	6.7	6.5	6.2	6.9	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.6	6.4	6.2	6.1	5.9
	横方向 (A)	縦方向 (B)	3.0	7.1	6.9	6.6	6.5	7.0	6.8	6.6	6.4	6.9	6.7	6.5	6.3	6.7	6.5	6.4	6.3	6.1
1.5m	2.74m	2.1m	4.0	7.3	7.1	6.9	6.7	7.2	7.0	6.8	6.7	7.0	6.9	6.7	6.6	6.9	6.7	6.6	6.5	6.3
2	3.66	2.66	5.0	7.4	7.2	7.1	6.9	7.3	7.1	7.0	6.9	7.1	7.0	6.9	6.8	7.0	6.8	6.8	6.7	6.5
2.5	4.57	3.22	7.0	7.5	7.4	7.2	7.1	7.4	7.3	7.2	7.1	7.2	7.1	7.0	7.0	7.1	7.0	6.9	6.8	6.7
3	5.49	3.8	10.0	7.5	7.5	7.4	7.3	7.5	7.4	7.3	7.2	7.3	7.2	7.2	7.1	7.1	7.1	7.0	7.0	6.8

