

屋内照明器具特性

品番 (品名)	XLGB1036	
光源	LLD20003CQ1 ×1	531.0 lm
管理番号	K0189935 (1) DR1	
BZ分類	BZ4/2.8/BZ5	

器具効率	87%	天井	80%				70%				50%				30%				0%		
	上方光束 5%		下方光束 82%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	50	40	34	29	49	39	33	29	46	38	33	29	44	37	32	28	26	
	中	0.63	0.8	59	49	43	38	57	49	42	38	54	47	41	37	52	45	41	37	35	
	否	0.56	1.0	64	56	49	45	63	55	49	44	60	53	48	44	57	51	46	43	40	
			1.25	69	61	55	51	67	60	55	50	64	58	53	49	61	56	52	48	46	
下方投影面積	cm ²		1.5	73	65	60	55	71	64	59	55	67	62	57	53	64	60	56	52	50	
	等価発光面積		cm ²	2.0	77	71	66	62	75	70	65	61	72	67	63	60	69	65	61	58	55
取付高さ	器具間隔最大限		2.5	80	75	70	66	78	73	69	65	75	70	67	64	71	68	65	62	59	
	横方向 (A)	縦方向 (B)	3.0	82	77	73	70	80	76	72	69	77	73	70	67	73	70	68	65	62	
Hm	1.30Hm	1.30Hm	4.0	84	81	77	74	82	79	76	73	79	76	74	71	76	74	71	69	66	
			5.0	86	83	80	77	84	81	79	76	81	78	76	74	78	76	74	72	68	
			7.0	88	85	83	81	86	84	82	80	83	81	79	77	79	78	77	75	72	
			10.0	89	87	86	84	87	86	84	83	84	83	81	80	81	80	79	78	74	

