

# 屋内照明器具特性

品番 (品名)	XLGB1118	
光源	LLD20001CQ1 ×1	531.0 lm
管理番号	K0186491(0)DR1	
BZ分類	BZ5	

器具効率	79%	天井	80%				70%				50%				30%				0%		
	上方光束		3%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		76%		床	10%				10%				10%				10%			
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.67	0.6	4.4	3.4	2.8	2.4	4.3	3.4	2.8	2.4	4.1	3.3	2.7	2.3	3.9	3.2	2.7	2.3	2.1	
	中	0.63	0.8	5.2	4.2	3.6	3.2	5.0	4.2	3.6	3.1	4.8	4.0	3.5	3.1	4.5	3.9	3.4	3.1	2.9	
	否	0.56	1.0	5.7	4.8	4.2	3.7	5.5	4.7	4.1	3.7	5.3	4.6	4.1	3.6	5.0	4.4	4.0	3.6	3.4	
			1.25	6.1	5.4	4.8	4.3	6.0	5.3	4.7	4.3	5.7	5.1	4.6	4.2	5.4	4.9	4.5	4.1	3.9	
下方投影面積	c m <sup>2</sup>		1.5	6.5	5.8	5.2	4.7	6.3	5.7	5.1	4.7	6.0	5.5	5.0	4.6	5.7	5.3	4.9	4.5	4.3	
	等価発光面積		c m <sup>2</sup>	2.0	6.9	6.3	5.8	5.4	6.8	6.2	5.7	5.4	6.5	6.0	5.6	5.2	6.2	5.8	5.4	5.2	4.9
取付高さ	器具間隔最大限		2.5	7.2	6.7	6.2	5.9	7.0	6.6	6.2	5.8	6.8	6.3	6.0	5.7	6.5	6.1	5.8	5.6	5.3	
	横方向 (A)	縦方向 (B)	3.0	7.4	6.9	6.5	6.2	7.2	6.8	6.5	6.1	7.0	6.6	6.3	6.0	6.7	6.4	6.1	5.9	5.6	
H m	1.12 H m	1.12 H m	4.0	7.7	7.3	7.0	6.7	7.5	7.2	6.9	6.6	7.2	6.9	6.7	6.4	6.9	6.7	6.5	6.3	6.0	
			5.0	7.8	7.5	7.2	7.0	7.7	7.4	7.1	6.9	7.4	7.1	6.9	6.7	7.1	6.9	6.7	6.6	6.3	
			7.0	8.0	7.8	7.6	7.4	7.9	7.6	7.4	7.3	7.6	7.4	7.2	7.1	7.3	7.2	7.0	6.9	6.6	
			10.0	8.1	8.0	7.8	7.7	8.0	7.8	7.7	7.6	7.7	7.6	7.5	7.4	7.5	7.4	7.3	7.2	6.9	

