

# 屋内照明器具特性

|         |                   |          |
|---------|-------------------|----------|
| 品番 (品名) | XLGB78671         |          |
| 光源      | LED3500_70_700 ×1 | 700.0 1m |
| 管理番号    | K0166927(1)D 1    |          |
| BZ分類    | BZ1               |          |

|        |                 |         |                 |        |        |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |
|--------|-----------------|---------|-----------------|--------|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|
| 器具効率   | 100%            | 天井      | 80%             |        |        |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |    |    |
|        | 上方光束<br>0%      |         | 反射率             | 70     | 50     | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |    |    |    |
| 下方光束   | 100%            | 床       |                 | 10%    |        |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |    |    |    |
| 室指数    | 照明率 ( X0.01 )   |         |                 |        |        |     |     |     |     |     |     |     |     |     |     |     |     |     |     | ZCM |    |    |    |
| 保守率    | 良 0.67          | 0.6     | 0.6             | 83     | 76     | 72  | 69  | 82  | 76  | 72  | 69  | 80  | 75  | 72  | 69  | 79  | 75  | 71  | 69  | 68  |    |    |    |
|        | 中 0.63          |         | 0.8             | 88     | 83     | 79  | 76  | 88  | 82  | 79  | 76  | 86  | 81  | 78  | 76  | 85  | 81  | 78  | 75  | 74  |    |    |    |
|        | 否 0.56          |         | 1.0             | 92     | 87     | 83  | 80  | 91  | 86  | 83  | 80  | 89  | 85  | 82  | 80  | 88  | 84  | 82  | 79  | 78  |    |    |    |
| 下方投影面積 | cm <sup>2</sup> | 等価発光面積  | cm <sup>2</sup> | 1.25   | 95     | 91  | 87  | 84  | 94  | 90  | 87  | 84  | 92  | 89  | 86  | 84  | 91  | 88  | 85  | 83  | 82 |    |    |
|        |                 |         |                 | 1.5    | 97     | 93  | 90  | 87  | 96  | 92  | 89  | 87  | 94  | 91  | 89  | 86  | 93  | 90  | 88  | 86  | 84 |    |    |
| 取付高さ   | 器具間隔最大限         |         | Hm              | 0.41Hm | 0.41Hm | 2.5 | 102 | 99  | 96  | 94  | 101 | 98  | 96  | 94  | 98  | 96  | 94  | 93  | 96  | 95  | 93 | 92 | 90 |
|        | 横方向 (A)         | 縦方向 (B) |                 |        |        | 3.0 | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 96  | 99  | 98  | 96  | 94  | 97  | 96  | 95 | 93 | 91 |
| Hm     | 0.41Hm          | 0.41Hm  | 4.0             | 104    | 102    | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 98  | 96  | 95  | 93  |    |    |    |
|        |                 |         | 5.0             | 105    | 103    | 102 | 100 | 104 | 102 | 101 | 100 | 102 | 100 | 99  | 98  | 100 | 99  | 98  | 97  | 94  |    |    |    |
| Hm     | 0.41Hm          | 0.41Hm  | 7.0             | 106    | 105    | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 100 | 99  | 98  | 96  |     |    |    |    |
|        |                 |         | 10.0            | 107    | 106    | 105 | 104 | 105 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 97  |    |    |    |

