

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLG432AGNJ ( J YOUJ I )      |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_3200 ×1 3200.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0177481 ( 0 ) D 1           |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                          |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                 |               |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
|--------|-----------------|---------------|------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 100 %           | 天井            | 80 % |      |      |     | 70 % |      |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |                 | 壁             | 70   | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
|        |                 | 床             | 10 % |      |      |     | 10 % |      |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 上方光束   | 4 %             | 室指数           |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
| 下方光束   | 96 %            | 照明率 ( X0.01 ) |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
|        |                 | ZCM           |      |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
| 保守率    | 良               | 0.83          | 0.6  | 5.5  | 4.3  | 3.5 | 3.0  | 5.4  | 4.2 | 3.5 | 3.0  | 5.1 | 4.1 | 3.4 | 2.9  | 4.9 | 4.0 | 3.3 | 2.9 | 2.7 |
|        | 中               | 0.81          | 0.8  | 6.5  | 5.4  | 4.5 | 4.0  | 6.4  | 5.3 | 4.5 | 3.9  | 6.0 | 5.1 | 4.4 | 3.9  | 5.7 | 4.9 | 4.3 | 3.8 | 3.6 |
|        | 否               | 0.77          | 1.0  | 7.2  | 6.1  | 5.3 | 4.7  | 7.0  | 6.0 | 5.2 | 4.7  | 6.6 | 5.8 | 5.1 | 4.6  | 6.3 | 5.6 | 5.0 | 4.5 | 4.3 |
|        |                 |               | 1.25 | 7.8  | 6.8  | 6.0 | 5.4  | 7.6  | 6.6 | 5.9 | 5.4  | 7.2 | 6.4 | 5.8 | 5.3  | 6.9 | 6.2 | 5.6 | 5.2 | 4.9 |
| 下方投影面積 | cm <sup>2</sup> |               | 1.5  | 8.2  | 7.2  | 6.5 | 6.0  | 8.0  | 7.1 | 6.4 | 5.9  | 7.6 | 6.9 | 6.3 | 5.8  | 7.3 | 6.6 | 6.1 | 5.7 | 5.4 |
| 等価発光面積 | cm <sup>2</sup> |               | 2.0  | 8.7  | 7.9  | 7.3 | 6.8  | 8.5  | 7.8 | 7.2 | 6.7  | 8.2 | 7.5 | 7.0 | 6.6  | 7.8 | 7.3 | 6.8 | 6.5 | 6.1 |
| 取付高さ   | 器具間隔最大限         |               | 2.5  | 9.1  | 8.4  | 7.8 | 7.3  | 8.9  | 8.3 | 7.7 | 7.3  | 8.5 | 8.0 | 7.5 | 7.1  | 8.2 | 7.7 | 7.3 | 7.0 | 6.6 |
|        | 横方向 (A)         | 縦方向 (B)       | 3.0  | 9.3  | 8.7  | 8.2 | 7.8  | 9.1  | 8.6 | 8.1 | 7.7  | 8.8 | 8.3 | 7.9 | 7.5  | 8.4 | 8.0 | 7.7 | 7.4 | 7.0 |
| 1.5m   | 1.96m           | 2.12m         | 4.0  | 9.7  | 9.2  | 8.7 | 8.4  | 9.5  | 9.0 | 8.6 | 8.3  | 9.1 | 8.7 | 8.4 | 8.1  | 8.8 | 8.4 | 8.2 | 7.9 | 7.5 |
| 2      | 2.58            | 2.66          | 5.0  | 9.9  | 9.5  | 9.1 | 8.7  | 9.7  | 9.3 | 9.0 | 8.6  | 9.3 | 9.0 | 8.7 | 8.4  | 9.0 | 8.7 | 8.5 | 8.2 | 7.9 |
| 2.5    | 3.21            | 3.22          | 7.0  | 10.1 | 9.8  | 9.5 | 9.2  | 9.9  | 9.6 | 9.4 | 9.1  | 9.6 | 9.3 | 9.1 | 8.9  | 9.2 | 9.0 | 8.8 | 8.7 | 8.3 |
| 3      | 3.84            | 3.8           | 10.0 | 10.3 | 10.0 | 9.8 | 9.6  | 10.1 | 9.9 | 9.7 | 9.5  | 9.8 | 9.6 | 9.4 | 9.2  | 9.4 | 9.3 | 9.1 | 9.0 | 8.6 |

