

屋内照明器具特性

品番 (品名)	XLX400SEN									
光源	LED5000_85_9730 x1					9730.0 lm				
管理番号	K0132112 (*) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	0 %	室指数																		照明率 (X0.01)																		ZCM																	
下方光束	100 %																																																						
保守率	良 中 否	0.81	0.6	5.6	4.3	3.5	3.0	5.4	4.2	3.5	2.9	5.2	4.1	3.4	2.9	5.0	4.0	3.4	2.9	2.7																																			
		0.77	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.5	4.0	6.1	5.1	4.5	3.9	5.9	5.0	4.4	3.9	3.7																																			
		0.68	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.3	4.7	6.7	5.8	5.2	4.6	6.5	5.7	5.1	4.6	4.4																																			
			1.25	7.8	6.8	6.0	5.4	7.6	6.7	6.0	5.4	7.3	6.5	5.9	5.4	7.0	6.3	5.8	5.3	5.1																																			
下方投影面積	c m ²	1.5	8.2	7.3	6.6	6.0	8.1	7.2	6.5	6.0	7.7	7.0	6.4	5.9	7.4	6.8	6.3	5.9	5.6																																				
		2.0	8.8	8.0	7.4	6.9	8.6	7.9	7.3	6.8	8.3	7.7	7.2	6.7	8.0	7.5	7.1	6.7	6.4																																				
取付高さ	器具間隔最大限		2.5	9.2	8.5	7.9	7.5	9.0	8.4	7.9	7.4	8.7	8.2	7.7	7.3	8.4	7.9	7.6	7.2	6.9																																			
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.9	9.3	8.7	8.3	7.8	9.0	8.5	8.1	7.7	8.7	8.3	7.9	7.6	7.3																																			
1.5m	1.98 m	2.17 m	4.0	9.8	9.3	8.9	8.5	9.6	9.2	8.8	8.4	9.3	8.9	8.6	8.3	9.0	8.7	8.4	8.2	7.9																																			
2	2.62	2.74	5.0	10.0	9.6	9.2	8.9	9.8	9.5	9.1	8.8	9.5	9.2	8.9	8.7	9.2	9.0	8.8	8.5	8.3																																			
2.5	3.25	3.32	7.0	10.2	9.9	9.6	9.4	10.1	9.8	9.5	9.3	9.8	9.5	9.3	9.1	9.5	9.3	9.1	9.0	8.7																																			
3	3.88	3.92	10.0	10.4	10.2	10.0	9.8	10.2	10.0	9.9	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.3	9.0																																			

