

# 屋内照明器具特性

品番 (品名)	XND0650WW	
光源	LED4000_85_625 ×1	625.0 lm
管理番号	K0159061(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	
上方光束	0%	壁	照明率 ( X0.01 )																ZCM
下方光束	100%	床	照明率 ( X0.01 )																ZCM
保守率	良 中 否	0.81 0.77 0.68	室指数																
			0.6	86	81	77	75	85	80	77	74	84	80	77	74	83	79	76	74
0.8	92	87	83	81	91	86	83	81	89	85	82	80	88	85	82	80	79		
1.0	95	90	87	85	94	90	87	85	92	89	86	84	91	88	86	84	83		
1.25	98	94	91	88	97	93	90	88	95	92	90	88	93	91	89	87	86		
1.5	99	96	93	91	98	95	93	91	97	94	92	90	95	93	91	89	88		
2.0	102	99	96	95	101	98	96	94	99	97	95	93	97	95	94	92	91		
2.5	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92		
3.0	104	102	100	99	103	101	99	98	101	99	98	97	99	98	97	96	94		
4.0	105	103	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95		
5.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	98	96		
7.0	107	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100	97		
10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98		

