

屋内照明器具特性

品番 (品名)	XND3530SW	
光源	LED4000_80_3975 ×1	3975.0 lm
管理番号	K0162736(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	床	10%				10%				10%				10%				0%			
下方光束	100%		室指数	照明率 (X0.01)																ZCM		
保守率	良	0.76	0.6	83	76	72	69	82	76	72	69	80	75	72	69	79	74	71	69	68		
	中	0.72	0.8	89	83	80	77	88	83	79	77	87	82	79	76	85	81	78	76	75		
	否	0.64	1.0	93	88	84	82	92	88	84	82	91	87	84	81	89	86	83	81	80		
下方投影面積	cm ²	等価発光面積	cm ²	1.25	96	92	89	86	95	91	88	86	94	90	88	85	92	89	87	85	83	
				1.5	98	95	92	89	97	94	91	89	96	93	90	88	94	91	89	87	86	86
取付高さ	器具間隔最大限		Hm	0.76Hm	0.76Hm	2.5	103	100	98	96	102	99	97	95	100	98	96	94	98	96	93	91
	横方向 (A)	縦方向 (B)				3.0	104	101	99	98	103	100	99	97	101	99	97	96	99	97	96	95
Hm	0.76Hm	0.76Hm	4.0	105	103	102	100	104	102	101	99	102	100	99	98	100	99	98	97	94	94	
			5.0	106	104	103	102	105	103	102	101	102	101	100	99	100	100	99	98	96	96	96
			7.0	107	105	104	104	105	104	104	103	103	102	102	101	101	100	99	97	97	97	
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98	98	

