

# 屋内照明器具特性

品番 (品名)	XND3531WV									
光源	LED3500_80_4060 x1 4060.0 1m									
管理番号	K0162733(0)DB1									
BZ分類	BZ2/0.7/BZ1/3.5/BZ2/8.5/BZ1									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.76	0.6	70	61	56	52	69	61	55	51	68	60	55	51	66	59	55	51	50
	中	0.72	0.8	80	72	67	63	79	71	66	62	77	70	66	62	75	69	65	62	60
	否	0.64	1.0	86	79	74	70	85	78	73	70	83	77	73	69	81	76	72	69	67
			1.25	90	84	80	76	89	84	79	76	87	82	78	75	85	81	78	75	73
下方投影面積	c m <sup>2</sup>		1.5	93	88	84	80	92	87	83	80	90	86	82	79	88	84	81	79	77
	等価発光面積		c m <sup>2</sup>	2.0	97	93	89	86	96	92	89	86	94	90	87	85	92	89	86	84
取付高さ	器具間隔最大限		2.5	99	96	93	90	98	95	92	90	96	93	91	89	94	91	89	88	85
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	94	92	97	95	93	91	95	93	91	90	88
H m	1.20 H m	1.20 H m	4.0	103	100	98	96	102	99	97	96	99	97	96	94	97	96	94	93	91
			5.0	104	102	100	98	103	101	99	98	100	99	97	96	98	97	96	95	92
			7.0	105	104	102	101	104	103	101	100	102	101	99	98	100	99	98	97	94
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	100	99	99	96

