

# 屋内照明器具特性

|         |                        |           |  |
|---------|------------------------|-----------|--|
| 品番 (品名) | XNG2060SWK ( J YOUJI ) |           |  |
| 光源      | LED4000_85_1820 ×1     | 1820.0 lm |  |
| 管理番号    | K0160267 ( 0 ) DB 1    |           |  |
| BZ分類    | BZ1                    |           |  |

|                  |                 |         |      |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     |     |     |
|------------------|-----------------|---------|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|------|------|-----|-----|-----|-----|
| 器具効率             | 100 %           | 天井      | 80 % |      |     |     | 70 % |      |     |     | 50 % |      |     |     | 30 % |      |     |     | 0 % |     |
|                  | 上方光束<br>0 %     |         | 反射率  | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10  | 0 % |
| 下方光束             | 100 %           | 床       |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |      | 10 % |     |     |     | 0 % |
| 室指数              | 照明率 ( X0.01 )   |         |      |      |     |     |      |      |     |     |      |      |     |     |      |      |     |     |     | ZCM |
| 保守率              | 良 0.81          | 0.6     | 86   | 81   | 77  | 75  | 86   | 81   | 77  | 75  | 84   | 80   | 77  | 75  | 83   | 79   | 77  | 75  | 74  |     |
|                  | 中 0.77          |         | 0.8  | 92   | 87  | 83  | 81   | 91   | 86  | 83  | 81   | 89   | 86  | 83  | 81   | 88   | 85  | 82  | 80  | 79  |
|                  | 否 0.68          |         | 1.0  | 95   | 91  | 88  | 85   | 94   | 90  | 87  | 85   | 93   | 89  | 87  | 85   | 91   | 88  | 86  | 84  | 83  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 98   | 94   | 91  | 89  | 97   | 93   | 91  | 89  | 95   | 92   | 90  | 88  | 94   | 91   | 89  | 87  | 86  |     |
|                  |                 | 1.5     | 99   | 96   | 93  | 91  | 98   | 95   | 93  | 91  | 97   | 94   | 92  | 90  | 95   | 93   | 91  | 90  | 88  |     |
| 取付高さ             | 器具間隔最大限         |         | 2.5  | 103  | 101 | 99  | 97   | 102  | 100 | 98  | 97   | 100  | 98  | 97  | 95   | 98   | 97  | 96  | 94  | 93  |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0  | 104  | 102 | 100 | 99   | 103  | 101 | 99  | 98   | 101  | 99  | 98  | 97   | 99   | 98  | 97  | 96  | 94  |
| Hm               | 0.82Hm          | 0.82Hm  | 4.0  | 105  | 103 | 102 | 101  | 104  | 102 | 101 | 100  | 102  | 101 | 100 | 99   | 100  | 99  | 98  | 97  | 95  |
|                  |                 |         | 5.0  | 106  | 104 | 103 | 102  | 105  | 103 | 102 | 101  | 102  | 102 | 101 | 100  | 101  | 100 | 99  | 98  | 96  |
|                  |                 |         | 7.0  | 106  | 105 | 105 | 104  | 105  | 104 | 104 | 103  | 103  | 102 | 102 | 101  | 101  | 101 | 100 | 100 | 97  |
|                  |                 |         | 10.0 | 107  | 106 | 106 | 105  | 106  | 105 | 105 | 104  | 104  | 103 | 103 | 102  | 102  | 101 | 101 | 101 | 98  |

