

屋内照明器具特性	
品番 (品名)	L G W8 0 1 5 9
光源	LED2700_70_383 ×1 383.0 l m
管理番号	K0130896 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		8 4 %																				
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 8	3 0	2 5	4 9	3 7	3 0	2 4	4 5	3 5	2 8	2 3	4 1	3 3	2 7	2 2	1 9	
			0 . 6	0 . 8	6 0	4 8	4 0	3 4	5 8	4 7	3 9	3 3	5 3	4 4	3 7	3 1	4 9	4 1	3 5	3 0	2 6	
			0 . 5 6	1 . 0	6 7	5 5	4 7	4 0	6 4	5 3	4 5	3 9	5 9	5 0	4 3	3 8	5 4	4 6	4 1	3 6	3 2	
				1 . 2 5	7 2	6 2	5 3	4 7	6 9	6 0	5 2	4 6	6 4	5 6	4 9	4 4	5 9	5 2	4 6	4 2	3 7	
下方投影面積		cm ²	1 . 5	7 7	6 6	5 9	5 2	7 3	6 4	5 7	5 1	6 8	6 0	5 4	4 9	6 2	5 6	5 1	4 6	4 1		
等価発光面積		cm ²	2 . 0	8 2	7 4	6 6	6 0	7 9	7 1	6 5	5 9	7 3	6 6	6 1	5 6	6 8	6 2	5 7	5 3	4 8		
取付 高さ	器具間隔最大限		2 . 5	8 6	7 8	7 2	6 6	8 3	7 6	7 0	6 5	7 7	7 1	6 6	6 1	7 1	6 6	6 2	5 8	5 3		
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 2	7 6	7 1	8 5	7 9	7 4	6 9	7 9	7 4	7 0	6 5	7 4	6 9	6 6	6 2	5 6		
H m	1 . 3 4 H m	1 . 3 2 H m	4 . 0	9 2	8 6	8 1	7 7	8 9	8 4	7 9	7 5	8 3	7 8	7 5	7 1	7 7	7 4	7 0	6 7	6 1		
			5 . 0	9 4	8 9	8 5	8 1	9 1	8 7	8 3	7 9	8 5	8 1	7 8	7 5	7 9	7 6	7 4	7 1	6 4		
			7 . 0	9 7	9 3	9 0	8 6	9 4	9 0	8 7	8 4	8 8	8 5	8 2	8 0	8 2	8 0	7 8	7 5	6 9		
			1 0 . 0	9 9	9 6	9 3	9 1	9 6	9 3	9 1	8 8	9 0	8 8	8 6	8 4	8 4	8 3	8 1	7 9	7 2		

