

屋内照明器具特性	
品番 (品名)	L G W8 0 1 9 0
光源	L G W8 0 1 9 0 (H1) ×1 1 0 6 2 . 0 l m
管理番号	K 0 1 2 7 9 7 0 (0) D B 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		1 9 % 8 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	5 0	3 8	3 0	2 4	4 8	3 6	2 9	2 3	4 4	3 4	2 7	2 2	4 0	3 1	2 5	2 1	1 8
			0 . 6	0 . 8	6 0	4 7	3 9	3 3	5 7	4 6	3 8	3 2	5 2	4 2	3 6	3 0	4 7	3 9	3 3	2 9	2 5
			0 . 5 6	1 . 0	6 6	5 4	4 6	4 0	6 3	5 2	4 5	3 9	5 8	4 9	4 2	3 7	5 2	4 5	3 9	3 5	3 0
			1 . 2 5	7 2	6 1	5 3	4 7	6 9	5 9	5 1	4 5	6 3	5 5	4 8	4 3	5 7	5 1	4 5	4 1	3 6	
下方投影面積		c m ²	1 . 5	7 6	6 6	5 8	5 2	7 3	6 4	5 6	5 1	6 7	5 9	5 3	4 8	6 1	5 5	5 0	4 5	4 0	
等価発光面積			c m ²	2 . 0	8 2	7 3	6 6	6 0	7 8	7 1	6 4	5 9	7 2	6 6	6 0	5 5	6 6	6 1	5 6	5 2	4 6
取付 高さ	器具間隔最大限		2 . 5	8 6	7 8	7 2	6 6	8 2	7 5	6 9	6 4	7 6	7 0	6 5	6 1	7 0	6 5	6 1	5 7	5 1	
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 1	7 6	7 1	8 5	7 9	7 3	6 9	7 8	7 3	6 9	6 5	7 2	6 8	6 4	6 1	5 4	
1 . 5m	2 . 3 m	1 . 9 6 m	4 . 0	9 2	8 6	8 1	7 7	8 8	8 3	7 9	7 5	8 2	7 7	7 4	7 0	7 5	7 2	6 9	6 6	5 9	
2	3 . 0 6	2 . 5 8	5 . 0	9 4	8 9	8 5	8 1	9 0	8 6	8 2	7 9	8 4	8 0	7 7	7 4	7 8	7 5	7 2	7 0	6 2	
2 . 5	3 . 8 4	3 . 2 1	7 . 0	9 6	9 3	8 9	8 6	9 3	9 0	8 7	8 4	8 7	8 4	8 1	7 9	8 0	7 8	7 6	7 4	6 7	
3	4 . 6	3 . 8 4	1 0 . 0	9 8	9 6	9 3	9 1	9 5	9 3	9 0	8 8	8 9	8 7	8 5	8 3	8 3	8 1	7 9	7 8	7 0	

