

屋内照明器具特性

品番 (品名)	LGB15164W				
光源	LED2700_70_782	x1	782.0	lm	
管理番号	K0134267(0)DB1				
BZ分類	BZ5/1.4/BZ4/3.5/BZ5				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		20%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		80%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.4	4.2	3.5	3.0	5.2	4.1	3.4	2.9	4.8	3.8	3.2	2.8	4.4	3.6	3.0	2.7	2.3	
	中	0.63	0.8	6.4	5.3	4.5	4.0	6.1	5.1	4.4	3.9	5.6	4.8	4.2	3.7	5.2	4.5	3.9	3.5	3.2	
	否	0.56	1.0	7.0	6.0	5.3	4.7	6.7	5.8	5.1	4.6	6.2	5.4	4.8	4.4	5.7	5.1	4.6	4.2	3.7	
			1.25	7.6	6.7	6.0	5.5	7.3	6.5	5.8	5.3	6.7	6.0	5.5	5.1	6.2	5.6	5.2	4.8	4.3	
下方投影面積			1.5	8.0	7.2	6.5	6.0	7.7	6.9	6.3	5.9	7.1	6.5	6.0	5.6	6.6	6.0	5.6	5.3	4.7	
	等価発光面積		2.0	8.6	7.9	7.3	6.8	8.2	7.6	7.1	6.6	7.6	7.1	6.7	6.3	7.0	6.6	6.3	6.0	5.4	
取付高さ	器具間隔最大限		2.5	8.9	8.3	7.8	7.4	8.6	8.0	7.6	7.2	7.9	7.5	7.1	6.8	7.3	7.0	6.7	6.4	5.8	
	横方向 (A)	縦方向 (B)	3.0	9.1	8.6	8.2	7.8	8.8	8.3	7.9	7.6	8.2	7.8	7.5	7.2	7.6	7.3	7.0	6.7	6.1	
Hm	1.30Hm	1.30Hm	4.0	9.4	9.0	8.7	8.3	9.1	8.7	8.4	8.1	8.5	8.2	7.9	7.6	7.8	7.6	7.4	7.2	6.5	
			5.0	9.6	9.3	9.0	8.7	9.3	9.0	8.7	8.4	8.6	8.4	8.2	7.9	8.0	7.8	7.6	7.5	6.7	
			7.0	9.8	9.6	9.3	9.1	9.5	9.3	9.0	8.8	8.8	8.7	8.5	8.3	8.2	8.1	7.9	7.8	7.0	
			10.0	10.0	9.8	9.6	9.5	9.7	9.5	9.3	9.2	9.0	8.9	8.7	8.6	8.4	8.3	8.2	8.1	7.3	

