

# 屋内照明器具特性

|         |   |          |  |  |  |
|---------|---|----------|--|--|--|
| 品番 (品名) | LGB15364                                |          |  |  |  |
| 光源      | LDA6L/C ×1                              | 485.0 lm |  |  |  |
| 管理番号    | K0134193(0)DB1                          |          |  |  |  |
| BZ分類    | BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5<br>/8.5/BZ6 |          |  |  |  |

|                |                    |                    |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    |     |
|----------------|--------------------|--------------------|------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率           | 91%                | 天井                 | 80%  |     |    |    | 70% |     |    |    | 50% |     |    |    | 30% |     |    |    | 0% |     |
|                | 上方光束<br>28%        |                    | 壁    | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束           | 63%                | 床                  |      | 10% |    |    |     | 10% |    |    |     | 10% |    |    |     | 10% |    |    |    | 0%  |
| 室指数            | 照明率 (X0.01)        |                    |      |     |    |    |     |     |    |    |     |     |    |    |     |     |    |    |    | ZCM |
| 保守率            | 良                  | 0.69               | 0.6  | 46  | 35 | 28 | 23  | 43  | 33 | 27 | 22  | 38  | 30 | 25 | 21  | 34  | 27 | 23 | 19 | 16  |
|                | 中                  | 0.67               | 0.8  | 54  | 44 | 36 | 31  | 51  | 42 | 35 | 30  | 45  | 38 | 32 | 28  | 40  | 34 | 29 | 26 | 21  |
|                | 否                  | 0.63               | 1.0  | 60  | 50 | 43 | 37  | 56  | 47 | 41 | 36  | 50  | 43 | 37 | 33  | 44  | 39 | 34 | 31 | 25  |
|                |                    |                    | 1.25 | 65  | 56 | 49 | 44  | 61  | 53 | 47 | 42  | 55  | 48 | 43 | 39  | 48  | 43 | 39 | 35 | 30  |
| 下方投影面積         | cm <sup>2</sup>    |                    | 1.5  | 69  | 60 | 54 | 48  | 65  | 57 | 51 | 47  | 58  | 52 | 47 | 43  | 51  | 47 | 43 | 39 | 33  |
| 等価発光面積         | cm <sup>2</sup>    |                    | 2.0  | 74  | 66 | 61 | 56  | 70  | 63 | 58 | 54  | 62  | 57 | 53 | 49  | 55  | 51 | 48 | 45 | 38  |
| 取付高さ           | 器具間隔最大限            |                    | 2.5  | 77  | 71 | 65 | 61  | 73  | 67 | 63 | 58  | 65  | 61 | 57 | 54  | 58  | 55 | 52 | 49 | 41  |
|                | 横方向 (A)            | 縦方向 (B)            | 3.0  | 79  | 74 | 69 | 65  | 75  | 70 | 66 | 62  | 67  | 63 | 60 | 57  | 60  | 57 | 54 | 52 | 44  |
| H <sub>m</sub> | 1.29H <sub>m</sub> | 1.29H <sub>m</sub> | 4.0  | 82  | 78 | 74 | 70  | 78  | 74 | 70 | 67  | 70  | 67 | 64 | 62  | 63  | 60 | 58 | 56 | 47  |
|                |                    |                    | 5.0  | 84  | 80 | 77 | 74  | 80  | 76 | 73 | 71  | 72  | 69 | 67 | 65  | 65  | 62 | 61 | 59 | 50  |
|                |                    |                    | 7.0  | 86  | 83 | 81 | 78  | 82  | 79 | 77 | 75  | 74  | 72 | 70 | 68  | 67  | 65 | 64 | 62 | 53  |
|                |                    |                    | 10.0 | 88  | 86 | 84 | 82  | 84  | 82 | 80 | 78  | 76  | 74 | 73 | 71  | 68  | 67 | 66 | 65 | 55  |

