

# 屋内照明器具特性

品番 (品名)	LGB52681									
光源	LED2700_70_2260 x1 2260.0 1m									
管理番号	K0140349(0)DR1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	56	43	36	30	54	43	35	30	51	41	34	29	48	39	33	29	27
	中	0.6	0.8	65	54	46	40	63	53	45	40	60	51	44	39	57	49	43	38	36
	否	0.56	1.0	72	61	53	48	70	60	53	47	66	57	51	46	62	55	50	45	42
			1.25	78	68	61	55	76	66	60	54	71	64	58	53	68	61	56	52	49
下方投影面積	cm <sup>2</sup>		1.5	82	73	66	60	80	71	65	60	75	68	63	58	71	66	61	57	53
等価発光面積	cm <sup>2</sup>		2.0	87	80	74	68	85	78	72	68	81	75	70	66	77	72	68	64	60
取付高さ	器具間隔最大限		2.5	91	84	79	74	89	83	77	73	84	79	75	71	80	76	72	69	65
	横方向 (A)	縦方向 (B)	3.0	93	87	83	78	91	86	81	77	87	82	78	75	83	79	76	73	69
Hm	1.25Hm	1.25Hm	4.0	96	92	88	84	94	90	86	83	90	86	83	80	86	83	80	78	74
			5.0	98	94	91	88	96	93	89	86	92	89	86	84	88	86	83	81	77
			7.0	101	98	95	92	98	96	93	91	94	92	90	88	90	89	87	85	81
			10.0	102	100	98	96	100	98	96	95	96	95	93	91	92	91	90	88	84

