

屋内照明器具特性	
品番 (品名)	NNN71500
光源	NNU240115KLE9 x1 1840.0 lm
管理番号	K0190784 (0) DB 1
B Z 分類	BZ2

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	62	53	47	43	61	52	47	43	59	52	47	43	57	51	46	43	41
			0.77	0.8	71	63	57	54	70	62	57	53	68	61	57	53	66	60	56	53	51
			0.68	1.0	76	69	64	60	75	69	64	60	73	67	63	60	71	66	63	60	58
				1.25	81	75	70	66	80	74	70	66	78	73	69	66	76	71	68	65	64
下方投影面積 等価発光面積		cm ²		1.5	84	78	74	71	83	78	74	70	80	76	73	70	78	75	72	69	67
				2.0	88	83	79	76	86	82	79	76	84	81	78	75	82	79	77	74	73
				2.5	90	86	83	80	89	85	82	80	86	84	81	79	84	82	80	78	76
取付 高さ	器具間隔最大限		3.0	91	88	85	83	90	87	85	82	88	85	83	81	86	84	82	80	78	
	横方向 (A)	縦方向 (B)		93	91	88	86	92	90	88	86	90	88	86	85	88	86	85	83	81	
H m	1.19 H m	1.19 H m	4.0	94	92	90	89	93	91	90	88	91	89	88	87	89	88	86	85	83	
			5.0	96	94	93	91	95	93	92	91	92	91	90	89	90	89	89	88	85	
			7.0	97	96	95	94	96	95	94	93	93	93	92	91	91	91	90	89	87	
			10.0																		

