

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 0
光源	NNU141105KLE9 ×1 1130.0 l m
管理番号	K0190793 (0) DB 1
B Z 分類	BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.81	0.6	60	51	46	42	59	51	45	42	57	50	45	41	56	49	45	41	40
			0.77	0.8	68	60	55	51	67	60	55	51	65	59	54	50	63	58	54	50	49
			0.68	1.0	74	66	61	57	72	66	61	57	70	65	60	57	68	63	60	56	55
				1.25	78	72	67	63	77	71	66	63	75	70	66	62	73	68	65	62	60
下方投影面積 等価発光面積		c m ² c m ²		1.5	81	75	71	67	80	75	71	67	78	73	70	67	76	72	69	66	64
				2.0	85	80	77	73	84	80	76	73	82	78	75	72	80	76	74	72	70
				2.5	87	83	80	77	86	83	80	77	84	81	78	76	82	79	77	75	73
取付 高さ	器具間隔最大限			3.0	89	86	83	80	88	85	82	80	86	83	81	79	83	81	79	78	76
	横方向 (A)	縦方向 (B)		4.0	91	88	86	84	90	87	85	83	88	86	84	82	86	84	82	81	79
H m	0.72 H m	0.72 H m		5.0	92	90	88	86	91	89	87	85	89	87	86	84	87	85	84	83	81
				7.0	93	92	90	89	92	91	89	88	90	89	88	87	88	87	86	85	83
				10.0	94	93	92	91	93	92	91	90	91	90	90	89	89	89	88	87	85

