

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 1
光源	NNU141105KLE9 x1 1130.0 l m
管理番号	K0190805 (0) DB 1
B Z 分類	BZ2

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	61	52	46	42	60	51	46	42	58	51	46	42	56	50	45	42	40
			0.77	0.8	69	61	56	52	68	61	55	52	66	60	55	51	64	59	54	51	50
			0.68	1.0	75	68	62	58	74	67	62	58	72	66	61	58	70	65	61	58	56
				1.25	79	73	68	64	78	72	68	64	76	71	67	64	74	70	66	63	62
下方投影面積 等価発光面積		cm ² cm ²		1.5	83	77	72	69	81	76	72	69	79	75	71	68	77	73	70	67	66
				2.0	87	82	78	75	85	81	77	74	83	79	76	74	81	78	75	73	71
				2.5	89	85	82	79	88	84	81	78	86	82	80	77	83	81	79	77	75
取付 高さ	器具間隔最大限		3.0	91	87	84	82	89	86	84	81	87	84	82	80	85	83	81	79	77	
	横方向 (A)	縦方向 (B)																			
H m	0.72 H m	0.72 H m	4.0	93	90	88	85	91	89	87	85	89	87	85	84	87	85	84	82	80	
			5.0	94	92	90	88	93	91	89	87	90	89	87	86	88	87	86	84	82	
			7.0	95	93	92	91	94	92	91	90	92	91	89	88	90	89	88	87	84	
			10.0	96	95	94	93	95	94	93	92	93	92	91	90	91	90	89	89	86	

