

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 3
光源	NNU241115KLE9 x1 1840.0 l m
管理番号	K0190822 (0) DB 1
B Z 分類	BZ2

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	63	54	48	44	62	53	48	44	60	52	47	43	58	52	47	43	42
			0.77	0.8	72	63	58	53	71	63	57	53	68	62	57	53	67	61	56	53	51
			0.68	1.0	77	70	64	60	76	69	64	60	74	68	63	60	72	67	63	60	58
				1.25	82	75	70	67	81	75	70	66	79	73	69	66	76	72	68	65	64
下方投影面積 等価発光面積		c m ²		1.5	85	79	75	71	84	79	74	71	82	77	73	70	80	76	73	70	68
				2.0	89	85	81	78	88	84	80	77	86	82	79	76	84	81	78	76	74
				2.5	92	88	84	82	91	87	84	81	88	85	83	80	86	84	81	79	77
				3.0	93	90	87	84	92	89	86	84	90	87	85	83	88	86	84	82	80
H m	0.71 H m	0.71 H m	4.0	95	93	90	88	94	92	90	88	92	90	88	86	90	88	87	85	83	
			5.0	97	94	92	91	95	93	92	90	93	92	90	89	91	90	88	87	85	
			7.0	98	96	95	94	97	95	94	93	95	93	92	91	93	92	91	90	87	
			10.0	99	98	97	96	98	97	96	95	96	95	94	93	94	93	92	92	89	

