

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 3
光源	NNU140165KLE9 x1 1450.0 l m
管理番号	K0190824 (0) DB 1
B Z 分類	BZ2

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		95 %																						
保守率		良 中 否	0.81	0.6	64	54	48	44	63	54	48	44	61	53	48	44	59	52	47	44	42			
			0.77	0.8	73	65	59	55	72	65	59	55	70	63	59	55	68	62	58	55	53			
			0.68	1.0	79	72	67	63	78	71	66	63	76	70	66	62	74	69	65	62	60			
				1.25	84	78	73	69	83	77	73	69	81	76	72	68	79	74	71	68	66			
下方投影面積		c m ²	1.5	87	82	77	74	86	81	77	73	84	79	76	73	82	78	75	72	70				
等価発光面積			c m ²	2.0	91	87	83	80	90	86	82	79	88	84	81	79	86	83	80	78	76			
				2.5	94	90	86	84	92	89	86	83	90	87	85	82	88	85	83	81	79			
取付 高さ	器具間隔最大限		2.5	94	90	86	84	92	89	86	83	90	87	85	82	88	85	83	81	79				
	横方向 (A)		縦方向 (B)		3.0	95	92	89	86	94	91	88	86	92	89	87	85	90	87	86	84	82		
H m	1.16 H m		1.16 H m		4.0	97	95	92	90	96	94	91	90	94	92	90	88	92	90	88	87	85		
					5.0	98	96	94	92	97	95	93	92	95	93	92	90	93	91	90	89	87		
					7.0	100	98	97	95	98	97	96	94	96	95	94	93	94	93	92	91	89		
					10.0	101	99	98	97	99	98	97	97	97	96	96	95	95	94	94	93	91		

