

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 3
光源	NNU141105KLE9 x1 1130.0 l m
管理番号	K0190829 (0) DB 1
B Z 分類	BZ2

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 93 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.81	0.6	62	53	47	43	61	52	47	43	59	52	46	43	58	51	46	43	41	
			0.77	0.8	71	63	57	53	70	62	57	53	68	61	56	52	66	60	56	52	51	
			0.68	1.0	77	69	64	60	76	69	63	60	73	67	63	59	71	66	62	59	57	
				1.25	82	75	70	66	80	74	69	66	78	73	69	65	76	71	68	65	63	
下方投影面積		cm ²	1.5	85	79	74	71	84	78	74	70	81	77	73	70	79	75	72	69	67		
等価発光面積		cm ²	2.0	89	84	80	77	88	83	80	77	85	82	78	76	83	80	77	75	73		
取付 高さ	器具間隔最大限		2.5	91	87	84	81	90	86	83	81	88	85	82	80	86	83	81	79	77		
	横方向 (A) 縦方向 (B)		3.0	93	90	87	84	92	89	86	83	89	87	84	82	87	85	83	81	79		
H m	0.71 H m	0.71 H m	4.0	95	92	90	88	94	91	89	87	92	89	88	86	89	88	86	85	82		
			5.0	96	94	92	90	95	93	91	90	93	91	90	88	91	89	88	87	84		
			7.0	98	96	95	93	96	95	94	92	94	93	92	91	92	91	90	89	87		
			10.0	99	97	96	95	97	96	95	95	95	94	94	93	93	93	92	91	89		

