

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 9 3
光源	LED2700_70_342 ×1 342.0 lm
管理番号	K0145066 (0) DB 1
BZ分類	BZ4 / 1.1 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 7 % 8 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 3	4 4	3 8	3 4	4 9	4 2	3 7	3 3	3 0	
			0 . 6 3	0 . 8	6 6	5 6	4 8	4 3	6 4	5 4	4 7	4 2	5 9	5 1	4 5	4 1	5 5	4 8	4 3	3 9	3 6	
			0 . 5 6	1 . 0	7 2	6 2	5 4	4 9	6 9	6 0	5 3	4 8	6 4	5 6	5 1	4 6	6 0	5 3	4 8	4 4	4 0	
			1 . 2 5	7 7	6 8	6 0	5 5	7 4	6 6	5 9	5 4	6 9	6 2	5 6	5 2	6 4	5 8	5 3	5 0	4 5		
下方投影面積		cm ²	1 . 5	8 1	7 2	6 5	6 0	7 8	7 0	6 4	5 8	7 2	6 6	6 0	5 6	6 7	6 2	5 7	5 4	4 9		
等価発光面積		cm ²	2 . 0	8 6	7 8	7 2	6 7	8 2	7 6	7 0	6 5	7 7	7 1	6 7	6 3	7 1	6 7	6 3	6 0	5 4		
取付 高さ	器具間隔最大限		2 . 5	8 9	8 2	7 7	7 2	8 6	8 0	7 5	7 0	8 0	7 5	7 1	6 7	7 4	7 0	6 7	6 4	5 8		
	横方向 (A) 縦方向 (B)		3 . 0	9 1	8 5	8 0	7 6	8 8	8 3	7 8	7 4	8 2	7 8	7 4	7 1	7 6	7 3	7 0	6 7	6 1		
H m	1 . 0 1 H m	1 . 0 1 H m	4 . 0	9 4	8 9	8 5	8 1	9 1	8 7	8 3	7 9	8 5	8 1	7 8	7 5	7 9	7 6	7 4	7 1	6 5		
			5 . 0	9 6	9 2	8 8	8 5	9 3	8 9	8 6	8 3	8 7	8 4	8 1	7 8	8 1	7 9	7 6	7 4	6 8		
			7 . 0	9 8	9 5	9 2	8 9	9 5	9 2	9 0	8 7	8 9	8 7	8 5	8 2	8 3	8 1	8 0	7 8	7 1		
			1 0 . 0	1 0 0	9 7	9 5	9 3	9 7	9 5	9 3	9 1	9 1	8 9	8 7	8 6	8 5	8 4	8 2	8 1	7 4		

