

屋内照明器具特性	
品番 (品名)	NNN6 1 5 2 2 W
光源	LDA7 L - H / S / 6 × 1 810.0 l m
管理番号	K0178365 (0) DB 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	44	36	31	28	43	36	31	28	42	35	31	28	40	35	30	27	26
			0.63	0.8	52	44	39	36	51	44	39	36	49	43	39	35	47	42	38	35	34
			0.56	1.0	56	50	45	41	55	49	45	41	53	48	44	41	52	47	44	41	39
				1.25	60	55	50	47	59	54	50	46	57	53	49	46	56	52	48	46	44
下方投影面積 等価発光面積		cm ² cm ²		1.5	63	58	54	50	62	57	53	50	60	56	53	50	58	55	52	49	48
				2.0	67	62	59	56	66	62	58	56	64	60	57	55	62	59	57	54	53
				2.5	69	65	62	59	68	65	62	59	66	63	61	58	64	62	60	58	56
取付 高さ	器具間隔最大限			3.0	70	67	64	62	69	66	64	62	67	65	63	61	66	64	62	60	58
	横方向 (A)	縦方向 (B)		4.0	72	70	68	66	71	69	67	65	69	67	66	64	68	66	65	63	61
H m	1.28 H m	1.28 H m		5.0	73	71	69	68	72	71	69	67	71	69	68	66	69	68	66	65	63
				7.0	75	73	72	70	74	72	71	70	72	71	70	69	70	69	68	67	66
				10.0	76	75	74	73	75	74	73	72	73	72	71	71	71	71	70	69	67

