

屋内照明器具特性	
品番 (品名)	L G B 8 0 5 5 4
光源	LED3500_70_228 ×1 228.0 l m
管理番号	K0147465 (0) DB 1
B Z 分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ3

器具効率		100 % 上方光束 下方光束	100 % 0 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	43	33	26	22	37	28	23	19	25	20	16	13	14	11	9	8	0	
			0.6	0.8	51	41	34	29	43	35	30	25	29	24	21	18	17	14	12	11	0	
			0.56	1.0	56	47	40	35	48	41	35	31	33	28	25	22	19	16	14	13	0	
				1.25	61	53	47	42	53	46	40	36	36	32	28	26	21	18	17	15	0	
下方投影面積		c m ² c m ²		1.5	65	57	51	47	56	49	45	41	38	34	31	29	22	20	18	17	0	
等価発光面積			2.0	70	64	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0		
取付 高さ	器具間隔最大限		2.5	73	68	63	59	63	58	54	51	43	40	38	36	25	24	22	21	0		
	横方向 (A) 縦方向 (B)		3.0	75	70	66	63	65	61	57	54	45	42	40	38	26	25	24	23	0		
H m	0.00 H m	1.03 H m	4.0	78	74	71	68	67	64	61	59	46	44	43	41	27	26	25	24	0		
			5.0	80	76	74	71	69	66	64	62	48	46	45	43	28	27	26	25	0		
			7.0	82	79	77	75	70	68	67	65	49	48	47	46	28	28	27	27	0		
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	29	28	28	0		

