

屋内照明器具特性	
品番 (品名)	L S E B C 2 0 6 5
光源	LED3500_70_437 ×1 437.0 l m
管理番号	K0147134 (0) DB 1
B Z 分類	BZ5 / 1.4 / BZ4 / 6.0 / BZ5 / 8.5 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	5 7	4 5	3 8	3 2	5 6	4 5	3 7	3 2	5 4	4 4	3 7	3 2	5 2	4 3	3 6	3 2	3 0	
			0 . 6 3	0 . 8	6 7	5 6	4 8	4 3	6 6	5 5	4 8	4 3	6 3	5 4	4 7	4 2	6 1	5 3	4 7	4 2	4 0	
			1 . 0	7 4	6 4	5 6	5 0	7 3	6 3	5 6	5 0	7 0	6 1	5 5	5 0	6 7	6 0	5 4	4 9	4 7		
			0 . 5 6	1 . 2 5	8 0	7 1	6 3	5 8	7 8	7 0	6 3	5 8	7 5	6 8	6 2	5 7	7 3	6 6	6 1	5 7	5 4	
下方投影面積 等価発光面積		c m ²	1 . 5	8 4	7 6	6 9	6 3	8 3	7 5	6 8	6 3	8 0	7 3	6 7	6 3	7 7	7 1	6 6	6 2	6 0		
			2 . 0	9 0	8 3	7 7	7 2	8 8	8 2	7 6	7 1	8 5	7 9	7 5	7 1	8 2	7 8	7 3	7 0	6 7		
取付高さ		器具間隔最大限		2 . 5	9 3	8 7	8 2	7 8	9 2	8 6	8 1	7 7	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	7 3	
		横方向 (A) 縦方向 (B)		3 . 0	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6	
H m		1 . 2 4 H m 1 . 2 4 H m		4 . 0	9 9	9 5	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 7	8 4	8 2	
				5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	8 9	8 8	8 5	
				7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9	
				1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2	

