

屋内照明器具特性	
品番 (品名)	F Y Y 2 6 1 4 0
光源	LED4000_85_2300 ×1 2300.0 lm
管理番号	K0149006 (0) DB 1
B Z 分類	B Z 4

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.83	0.6	56	45	38	33	55	44	37	33	52	43	37	32	50	42	36	32	31
			0.81	0.8	65	55	48	43	64	55	48	43	62	53	47	43	59	52	47	43	41
			0.77	1.0	72	62	56	51	70	62	55	50	68	60	54	50	65	59	54	50	48
				1.25	77	69	63	58	76	68	62	57	73	66	61	57	71	65	60	57	55
下方投影面積		cm ²		1.5	81	74	68	63	80	73	67	63	77	71	66	62	74	69	65	61	59
			等価発光面積	cm ²	2.0	86	80	75	70	85	79	74	70	82	77	73	69	79	75	72	69
取付 高さ	器具間隔最大限			2.5	89	84	79	76	88	83	79	75	85	81	77	74	83	79	76	73	71
	横方向 (A) 縦方向 (B)			3.0	91	87	83	79	90	86	82	79	87	84	81	78	85	82	79	77	74
1.5m	1.96 m	2.25 m		4.0	94	90	87	84	93	89	86	84	90	87	85	82	88	85	83	81	79
2	2.61	2.9		5.0	96	93	90	88	94	92	89	87	92	90	87	85	90	88	86	84	82
2.5	3.26	3.57		7.0	98	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	85
3	3.9	4.25		10.0	99	97	96	94	98	96	95	94	95	94	93	92	93	92	91	90	88

