

屋内照明器具特性	
品番 (品名)	NNN1 6 4 4 0
光源	LDA13 L - G / Z100 E / S / W ×4 1520.0 l m
管理番号	K0158979 (0) DB 1
B Z 分類	B Z 9

器具効率		5 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		2 6 %	室指数	照明率 (X 0 . 0 1)																Z C M	
下方光束		2 5 %																			
保守率		良 中 否	0 . 6 9	0 . 6	2 2	1 6	1 2	9	2 0	1 4	1 1	8	1 6	1 2	9	7	1 3	1 0	7	5	3
			0 . 6 7	0 . 8	2 6	2 0	1 6	1 3	2 4	1 8	1 5	1 2	2 0	1 5	1 2	1 0	1 6	1 2	1 0	8	4
			0 . 6 3	1 . 0	2 9	2 3	1 9	1 6	2 7	2 1	1 7	1 4	2 2	1 8	1 4	1 2	1 7	1 4	1 2	1 0	6
				1 . 2 5	3 2	2 6	2 2	1 9	2 9	2 4	2 0	1 7	2 4	2 0	1 7	1 5	1 9	1 6	1 4	1 2	7
下方投影面積		cm ²	1 . 5	3 4	2 9	2 5	2 1	3 1	2 7	2 3	2 0	2 6	2 2	1 9	1 7	2 1	1 8	1 5	1 3	8	
等価発光面積		cm ²	2 . 0	3 7	3 2	2 9	2 5	3 4	3 0	2 6	2 3	2 8	2 5	2 2	2 0	2 3	2 0	1 8	1 6	1 0	
取付 高さ	器具間隔最大限		2 . 5	3 9	3 5	3 1	2 8	3 6	3 2	2 9	2 6	3 0	2 7	2 4	2 2	2 4	2 2	2 0	1 8	1 2	
	横方向 (A)		縦方向 (B)	3 . 0	4 0	3 7	3 3	3 1	3 7	3 4	3 1	2 8	3 1	2 8	2 6	2 4	2 5	2 3	2 1	2 0	1 3
1 . 5m	2 . 1 4 m	2 . 3 4 m	4 . 0	4 2	3 9	3 6	3 4	3 9	3 6	3 4	3 1	3 3	3 0	2 8	2 7	2 7	2 5	2 3	2 2	1 5	
2	2 . 8 4	3 . 1	5 . 0	4 3	4 1	3 8	3 6	4 0	3 8	3 5	3 3	3 4	3 2	3 0	2 8	2 8	2 6	2 5	2 4	1 6	
2 . 5	3 . 5 1	3 . 8 6	7 . 0	4 5	4 3	4 1	3 9	4 1	3 9	3 8	3 6	3 5	3 3	3 2	3 1	2 9	2 8	2 7	2 6	1 8	
3	4 . 2 1	4 . 6 3	1 0 . 0	4 6	4 4	4 3	4 1	4 3	4 1	4 0	3 8	3 6	3 5	3 4	3 3	3 0	2 9	2 8	2 7	1 9	

