

屋内照明器具特性	
品番 (品名)	XL463PET
光源	LED3000_85_2700 ×1 2700.0lm
管理番号	K0128355 (＊)DB1
BZ分類	BZ5/8.5/BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束				100 %																				
保守率		良 中 否	0.81	0.6	56	44	36	31	55	44	36	31	53	43	36	31	51	41	35	31	29			
			0.77	0.8	67	55	47	41	65	54	47	41	62	53	46	41	60	52	45	41	39			
			0.68	1.0	73	63	55	49	72	62	54	49	69	60	54	48	66	59	53	48	46			
				1.25	79	70	62	57	78	69	62	56	75	67	61	56	72	65	60	56	53			
下方投影面積		cm ²	1.5	84	75	68	62	82	74	67	62	79	72	66	62	76	70	65	61	59				
			2.0	89	82	76	71	88	81	75	71	85	79	74	70	82	77	73	69	67				
等価発光面積		cm ²	2.5	93	87	82	77	91	86	81	77	88	84	79	76	86	82	78	75	72				
			3.0	96	90	85	81	94	89	85	81	91	87	83	80	88	85	82	79	76				
1.5m		1.95 m	1.93 m	4.0	99	94	91	87	97	93	90	87	94	91	88	85	92	89	86	84	81			
2		2.55	2.52	5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	92	89	88	85			
2.5		3.19	3.15	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89			
3		3.83	3.78	10.0	104	103	101	99	103	101	100	98	101	99	98	96	98	97	96	95	92			

