

屋内照明器具特性	
品番 (品名)	XL 3 6 3 C B F
光源	LED3500_85_2660 ×1 2660.0 lm
管理番号	K0128355 (*) DB 1
B Z 分類	BZ5 / 8.5 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 8 1	0 . 6	5 6	4 4	3 6	3 1	5 5	4 4	3 6	3 1	5 3	4 3	3 6	3 1	5 1	4 1	3 5	3 1	2 9
			0 . 7 7	0 . 8	6 7	5 5	4 7	4 1	6 5	5 4	4 7	4 1	6 2	5 3	4 6	4 1	6 0	5 2	4 5	4 1	3 9
			1 . 0	7 3	6 3	5 5	4 9	7 2	6 2	5 4	4 9	6 9	6 0	5 4	4 8	6 6	5 9	5 3	4 8	4 6	
			0 . 6 8	1 . 2 5	7 9	7 0	6 2	5 7	7 8	6 9	6 2	5 6	7 5	6 7	6 1	5 6	7 2	6 5	6 0	5 6	5 3
下方投影面積		c m ²	1 . 5	8 4	7 5	6 8	6 2	8 2	7 4	6 7	6 2	7 9	7 2	6 6	6 2	7 6	7 0	6 5	6 1	5 9	
			等価発光面積		c m ²	2 . 0	8 9	8 2	7 6	7 1	8 8	8 1	7 5	7 1	8 5	7 9	7 4	7 0	8 2	7 7	7 3
取付 高さ	器具間隔最大限		2 . 5	9 3	8 7	8 2	7 7	9 1	8 6	8 1	7 7	8 8	8 4	7 9	7 6	8 6	8 2	7 8	7 5	7 2	
	横方向 (A) 縦方向 (B)		3 . 0	9 6	9 0	8 5	8 1	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6	
1 . 5m	1 . 9 5 m	1 . 9 2 m	4 . 0	9 9	9 4	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 1	
2	2 . 5 5	2 . 5 2	5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 2	8 9	8 8	8 5	
2 . 5	3 . 1 9	3 . 1 5	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9	
3	3 . 8 3	3 . 7 8	1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2	

