

屋内照明器具特性	
品番 (品名)	NNN1 1 2 3 0
光源	LDA4L-G-E17/K40E/S/W/2 ×1 440.0 1m
管理番号	K0159058(0)DB1
BZ分類	BZ6/0.7/BZ5/1.8/BZ6

器具効率	85 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	43 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	42 %	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.69	0.6	41	31	25	21	38	29	23	19	32	25	20	17	26	21	17	14	10
	中	0.67	0.8	48	39	33	28	45	36	30	26	37	31	26	23	31	26	22	20	14
	否	0.63	1.0	54	45	38	33	49	41	36	31	41	35	31	27	34	30	26	23	17
			1.25	58	50	44	39	54	46	41	37	45	40	35	32	37	33	30	27	20
下方投影面積			1.5	61	54	48	43	57	50	45	41	48	43	39	35	39	36	33	30	22
			2.0	66	59	54	50	61	55	51	47	51	47	44	40	43	39	37	34	25
取付高さ	器具間隔最大限		2.5	69	63	58	54	64	59	54	51	54	50	47	44	45	42	39	37	27
	横方向 (A)	縦方向 (B)	3.0	71	66	62	58	65	61	57	54	55	52	49	47	46	44	42	40	29
Hm	1.52Hm	1.64Hm	4.0	73	69	66	63	68	64	61	58	58	55	53	50	48	46	44	31	
			5.0	75	72	68	66	69	67	64	61	59	57	55	53	49	48	46	45	32
			7.0	77	74	72	70	71	69	67	65	61	59	58	56	51	50	48	47	34
			10.0	78	76	75	73	73	71	70	68	62	61	60	59	52	51	50	49	36

