

屋内照明器具特性	
品番 (品名)	L G W C 8 0 4 1 0
光源	LED2700_70_372 x1 372.0 lm
管理番号	K0160290 (0) DR 1
B Z 分類	B Z 1 0

器具効率	100 % 上方光束 50 % 下方光束 50 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数	照明率 (X 0.01)																Z C M
保守率	良 0.63	0.6	43	30	22	16	39	27	20	14	31	22	16	12	25	17	12	9	3
	中 0.6	0.8	51	38	29	23	46	35	27	21	37	28	22	17	29	22	17	13	6
	否 0.56	1.0	57	44	35	29	51	40	32	26	42	33	26	21	33	26	21	17	9
		1.25	62	50	42	35	56	46	38	32	46	38	31	26	36	30	25	21	11
下方投影面積 等価発光面積	cm ² cm ²	1.5	66	55	47	40	60	51	43	37	49	42	35	30	39	33	28	24	14
		2.0	72	62	54	48	66	57	50	44	54	47	42	37	43	38	33	30	18
		2.5	76	67	60	54	69	62	55	50	57	51	46	42	46	41	37	34	21
		3.0	79	71	64	58	72	65	59	54	60	54	50	45	48	44	40	37	24
取付高さ	器具間隔最大限 横方向 (A) 縦方向 (B)	4.0	82	76	70	65	76	70	65	60	63	59	54	51	51	48	45	42	27
H m	0.00 H m 0.00 H m	5.0	85	79	74	69	78	73	68	64	65	61	58	54	53	50	47	45	30
		7.0	88	83	79	75	81	77	73	70	68	65	62	59	56	54	51	49	34
		10.0	90	87	83	80	83	80	77	75	71	68	66	64	58	57	55	53	37

