

屋内照明器具特性

品番 (品名)	XLX200PEL				
光源	LED3000_85_700	x1	700.0	lm	
管理番号	K0137984(9)DB1				
BZ分類	BZ5/4.5/BZ4/6.0/BZ5/8.5/BZ4				

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床	10%				10%				10%				10%				0%		
室指数		照明率 (X0.01)																			ZCM
保守率	良	0.81	0.6	57	45	37	31	55	44	36	31	53	43	36	31	51	42	36	31	29	
	中	0.77	0.8	67	55	48	42	65	55	47	42	63	53	46	41	60	52	46	41	39	
	否	0.68	1.0	74	63	55	49	72	62	55	49	69	60	54	49	66	59	53	49	46	
			1.25	80	70	63	57	78	69	62	57	75	67	61	56	72	66	60	56	54	
下方投影面積		cm ²	1.5	84	75	68	63	82	74	68	63	79	72	67	62	76	70	65	61	59	
等価発光面積		cm ²	2.0	90	82	76	71	88	81	76	71	85	79	74	70	82	77	73	69	67	
取付高さ	器具間隔最大限		2.5	93	87	82	77	91	86	81	77	88	84	79	76	86	82	78	75	72	
	横方向 (A)	縦方向 (B)	3.0	96	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76	
1.5m	1.91m	1.95m	4.0	99	94	91	87	97	93	90	87	94	91	88	85	92	89	86	84	81	
2	2.54	2.56	5.0	101	97	94	91	99	96	93	90	96	94	91	89	94	91	89	87	85	
2.5	3.17	3.18	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	91	89	
3	3.81	3.8	10.0	104	103	101	99	103	101	100	98	100	99	98	96	98	97	96	95	92	

