

屋内照明器具特性	
品番 (品名)	XLX830TELC
光源	LED3000_85_11410 ×1 11410.0 lm
管理番号	K0129806 (2) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		2 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		98 %																							
保守率		良 中 否	0.83	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26				
			0.81	0.8	65	53	44	39	63	52	44	38	60	50	43	38	57	49	42	38	35				
			0.77	1.0	71	60	52	46	69	59	51	46	66	57	50	45	63	55	49	45	42				
				1.25	77	67	59	53	75	66	58	53	72	64	57	52	69	62	56	51	49				
下方投影面積		cm ²	1.5	81	72	65	59	79	71	64	58	76	68	62	57	73	66	61	57	54					
等価発光面積		cm ²	2.0	87	79	72	67	85	78	72	66	82	75	70	65	78	73	68	64	62					
取付 高さ	器具間隔最大限		2.5	91	84	78	73	89	82	77	72	85	80	75	71	82	77	73	70	67					
	横方向 (A)	縦方向 (B)	3.0	93	87	82	77	91	86	81	76	88	83	79	75	85	81	77	74	71					
1.5m	2.1 m	2.89 m	4.0	97	92	87	83	95	90	86	82	91	88	84	81	88	85	82	79	76					
2	2.74	3.34	5.0	99	94	91	87	97	93	90	86	94	90	87	85	91	88	85	83	80					
2.5	3.39	3.85	7.0	101	98	95	92	99	96	94	91	96	94	91	89	93	91	89	87	84					
3	4.03	4.4	10.0	103	101	98	96	101	99	97	95	98	96	95	93	95	94	92	91	88					

