

屋内照明器具特性	
品番 (品名)	XLX850AEVC
光源	LED3500_85_4660 ×1 4660.0 lm
管理番号	K0128261 (*) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		4 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		96 %																						
保守率		良 中 否	0.83	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25			
			0.81	0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	35			
			0.77	1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41			
				1.25	77	67	59	53	75	65	58	52	71	63	57	52	68	61	55	51	48			
下方投影面積		cm ²		1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53			
				2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60			
等価発光面積		cm ²		2.5	90	83	77	72	88	82	76	72	84	79	74	70	81	76	72	69	65			
				3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69			
1.5m		2.09 m	2.89 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74			
2		2.72	3.32	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	78			
2.5		3.36	3.82	7.0	101	97	94	92	99	96	93	90	95	93	90	88	92	89	88	86	82			
3		4	4.35	10.0	102	100	98	96	101	98	96	94	97	95	93	92	94	92	91	89	85			

