

屋内照明器具特性	
品番 (品名)	L G B 1 1 6 2 3
光源	LED6200_70_3150 ×1 3150.0 lm
管理番号	K0163261 (1) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 1.1 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 4 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		7 6 %																				
保守率		良 中 否	0 . 6 7	0 . 6	5 2	4 0	3 2	2 6	4 9	3 8	3 1	2 6	4 4	3 5	2 9	2 4	4 0	3 2	2 7	2 3	1 9	
			0 . 6 3	0 . 8	6 1	4 9	4 1	3 5	5 8	4 7	4 0	3 4	5 2	4 3	3 7	3 2	4 7	4 0	3 4	3 0	2 6	
			1 . 0	6 7	5 6	4 8	4 2	6 4	5 3	4 6	4 0	5 7	4 9	4 3	3 8	5 2	4 5	4 0	3 6	3 1		
			0 . 5 6	1 . 2 5	7 2	6 2	5 4	4 8	6 9	5 9	5 2	4 7	6 2	5 5	4 9	4 4	5 6	5 0	4 5	4 1	3 5	
下方投影面積		cm ²	1 . 5	7 6	6 7	5 9	5 3	7 3	6 4	5 7	5 2	6 6	5 9	5 3	4 8	5 9	5 4	4 9	4 5	3 9		
等価発光面積		cm ²	2 . 0	8 2	7 4	6 7	6 1	7 8	7 1	6 4	5 9	7 1	6 5	6 0	5 5	6 4	5 9	5 5	5 1	4 5		
取付 高さ	器具間隔最大限		2 . 5	8 5	7 8	7 2	6 7	8 1	7 5	6 9	6 5	7 4	6 9	6 4	6 0	6 7	6 3	5 9	5 6	4 9		
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 1	7 6	7 1	8 4	7 8	7 3	6 9	7 6	7 2	6 8	6 4	6 9	6 6	6 2	5 9	5 2		
H m	1 . 3 5 H m	1 . 3 5 H m	4 . 0	9 1	8 6	8 1	7 7	8 7	8 2	7 8	7 4	8 0	7 6	7 2	6 9	7 3	6 9	6 7	6 4	5 6		
			5 . 0	9 3	8 9	8 5	8 1	8 9	8 5	8 1	7 8	8 2	7 8	7 5	7 2	7 4	7 2	6 9	6 7	5 9		
			7 . 0	9 6	9 2	8 9	8 6	9 2	8 8	8 6	8 3	8 4	8 2	7 9	7 7	7 7	7 5	7 3	7 1	6 2		
			1 0 . 0	9 7	9 5	9 2	9 0	9 4	9 1	8 9	8 7	8 6	8 4	8 2	8 1	7 9	7 7	7 6	7 4	6 5		

