

屋内照明器具特性	
品番 (品名)	L G B 8 1 0 1 1
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 6 4 2 7 (0) D R 1
B Z 分類	B Z 1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		88 %																				
保守率		良	0 . 6 7	0 . 6	73	68	64	62	72	67	64	62	71	67	64	61	70	66	63	61	60	
		中	0 . 6 3	0 . 8	78	73	70	67	77	73	70	67	76	72	69	67	75	71	69	67	66	
		否	0 . 5 6	1 . 0	81	77	74	71	81	76	73	71	79	76	73	71	78	75	72	70	69	
				1 . 2 5	84	80	77	75	83	80	77	75	82	78	76	74	80	77	75	74	72	
下方投影面積		c m ²		1 . 5	86	82	80	77	85	82	79	77	83	81	78	76	82	79	78	76	75	
等価発光面積		c m ²		2 . 0	88	85	83	81	87	85	82	81	86	83	81	80	84	82	80	79	77	
取付高さ	器具間隔最大限			2 . 5	90	87	85	83	89	86	84	83	87	85	83	82	85	84	82	81	79	
	横方向 (A)		縦方向 (B)	3 . 0	91	88	87	85	90	88	86	84	88	86	85	83	86	85	83	82	81	
H m	0 . 4 2 H m		0 . 4 2 H m	4 . 0	92	90	89	87	91	89	88	87	89	88	86	85	87	86	85	84	82	
				5 . 0	92	91	90	89	91	90	89	88	90	89	88	87	88	87	86	85	83	
				7 . 0	93	92	91	90	92	91	90	90	90	90	89	88	88	88	87	87	85	
				10 . 0	94	93	92	92	93	92	92	91	91	90	90	89	89	89	88	88	85	

