

屋内照明器具特性	
品番 (品名)	F Y Y 2 2 7 3 0
光源	LED3000_85_910 ×1 910.0 lm
管理番号	K0166072 (0) DB 1
B Z 分類	BZ6 / 1.4 / BZ5

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	天井 壁 床 室指数	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				1 0 %				1 0 %				1 0 %				1 0 %				0 %
				照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 2	3 9	3 0	2 4	5 1	3 8	3 0	2 4	4 8	3 7	2 9	2 4	4 6	3 6	2 9	2 4	2 2
			0 . 8	6 2	4 9	4 1	3 4	6 1	4 9	4 0	3 4	5 8	4 7	4 0	3 4	5 5	4 6	3 9	3 4	3 2
			1 . 0	6 9	5 7	4 9	4 2	6 8	5 6	4 8	4 2	6 4	5 5	4 7	4 2	6 1	5 3	4 7	4 1	3 9
			0 . 7 7	1 . 2 5	7 6	6 5	5 7	5 0	7 4	6 4	5 6	5 0	7 1	6 2	5 5	5 0	6 8	6 0	5 4	4 9
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 1	7 1	6 3	5 7	7 9	7 0	6 2	5 7	7 5	6 8	6 1	5 6	7 2	6 6	6 0	5 5	5 3
			2 . 0	8 7	7 9	7 2	6 6	8 5	7 8	7 1	6 6	8 2	7 5	7 0	6 5	7 9	7 3	6 9	6 4	6 2
取付 高さ	器具間隔最大限		2 . 5	9 1	8 4	7 8	7 3	8 9	8 3	7 7	7 2	8 6	8 0	7 6	7 1	8 3	7 8	7 4	7 1	6 8
	横方向 (A)	縦方向 (B)	3 . 0	9 4	8 8	8 2	7 8	9 2	8 6	8 1	7 7	8 9	8 4	8 0	7 6	8 6	8 2	7 8	7 5	7 2
1 . 5m	0 m	2 . 0 1 m	4 . 0	9 7	9 2	8 8	8 4	9 6	9 1	8 7	8 4	9 3	8 9	8 5	8 2	9 0	8 7	8 4	8 1	7 8
2	0	2 . 6 6	5 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 2	9 0	8 7	8 5	8 2
2 . 5	0	3 . 3	7 . 0	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7
3	0	3 . 9 6	1 0 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 2	1 0 0	9 9	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 0

