

屋内照明器具特性	
品番 (品名)	L G D 1 0 0 1 N
光源	LED5000_70_335 ×1 335.0 l m
管理番号	K0151698 (0) D 1
B Z 分類	B Z 3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束				1 0 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	6 4	5 4	4 7	4 2	6 3	5 3	4 7	4 2	6 1	5 2	4 7	4 2	5 9	5 1	4 6	4 2	4 0			
			0 . 6 3	0 . 8	7 4	6 5	5 8	5 4	7 3	6 4	5 8	5 4	7 1	6 3	5 8	5 3	6 9	6 2	5 7	5 3	5 1			
			1 . 0	8 1	7 2	6 6	6 2	8 0	7 2	6 6	6 1	7 7	7 0	6 5	6 1	7 5	6 9	6 4	6 1	5 9				
			0 . 5 6	1 . 2 5	8 6	7 9	7 3	6 9	8 5	7 8	7 3	6 8	8 2	7 6	7 2	6 8	8 0	7 5	7 1	6 7	6 6			
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 4	8 8	8 2	7 7	7 3	8 6	8 1	7 6	7 3	8 3	7 9	7 5	7 2	7 0				
			2 . 0	9 4	8 9	8 4	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 3	7 9	8 8	8 4	8 1	7 9	7 7				
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 5	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1				
	横方向 (A) 縦方向 (B)		3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 3				
H m	1 . 1 5 H m	1 . 1 5 H m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7				
			5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	9 9	9 7	9 5	9 4	9 7	9 5	9 4	9 2	9 0				
			7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2				
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4				

