

屋内照明器具特性	
品番 (品名)	L G D 3 2 0 3 N
光源	LED5000_70_670 ×1 670.0 l m
管理番号	K0153097 (0) D 1
B Z 分類	B Z 4

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	5 9	4 8	4 0	3 5	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 4	4 5	3 9	3 5	3 3					
			0 . 6 3	0 . 8	7 0	5 9	5 1	4 6	6 8	5 8	5 1	4 6	6 6	5 7	5 0	4 6	6 3	5 5	5 0	4 5	4 3					
			1 . 0	1 . 0	7 6	6 6	5 9	5 4	7 5	6 5	5 9	5 3	7 2	6 4	5 8	5 3	6 9	6 2	5 7	5 3	5 1					
			0 . 5 6	1 . 2 5	8 2	7 3	6 6	6 1	8 1	7 2	6 6	6 1	7 8	7 1	6 5	6 1	7 5	6 9	6 4	6 0	5 8					
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	1 . 5	8 6	7 8	7 2	6 7	8 5	7 7	7 1	6 7	8 2	7 5	7 0	6 6	7 9	7 4	6 9	6 5	6 3					
			2 . 0	2 . 0	9 2	8 5	8 0	7 5	9 0	8 4	7 9	7 5	8 7	8 2	7 8	7 4	8 5	8 0	7 7	7 3	7 1					
			2 . 5	2 . 5	9 5	8 9	8 5	8 1	9 4	8 8	8 4	8 0	9 1	8 6	8 3	7 9	8 8	8 4	8 1	7 8	7 6					
取付 高さ	器具間隔最大限		3 . 0	3 . 0	9 7	9 3	8 8	8 5	9 6	9 1	8 8	8 4	9 3	8 9	8 6	8 3	9 1	8 7	8 5	8 2	8 0					
	横方向 (A)	縦方向 (B)	4 . 0	4 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 4	9 1	8 9	8 7	8 4					
H m	1 . 1 9 H m	1 . 1 9 H m	5 . 0	5 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 7					
			7 . 0	7 . 0	1 0 4	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 7	9 5	9 7	9 6	9 5	9 3	9 1					
			1 0 . 0	1 0 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 7	9 6	9 3					

