

屋内照明器具特性	
品番 (品名)	L G D 9 2 0 1
光源	L L D 4 0 0 0 L C S 1 × 1 8 3 0 . 0 l m
管理番号	K 0 1 8 1 8 6 7 (0) D R 1
B Z 分類	B Z 4 / 1 . 4 / B Z 3

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				上方光束 下方光束		8 7 %															
			室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	5 2	4 2	3 6	3 1	5 1	4 2	3 5	3 1	4 9	4 1	3 5	3 1	4 7	4 0	3 5	3 1	2 9
			0 . 6 3	0 . 8	6 1	5 2	4 6	4 1	6 0	5 2	4 6	4 1	5 8	5 0	4 5	4 1	5 6	4 9	4 4	4 1	3 9
			0 . 5 6	1 . 0	6 7	5 9	5 3	4 8	6 6	5 8	5 3	4 8	6 4	5 7	5 2	4 8	6 2	5 6	5 1	4 8	4 6
				1 . 2 5	7 3	6 5	5 9	5 5	7 1	6 4	5 9	5 5	6 9	6 3	5 8	5 4	6 7	6 2	5 7	5 4	5 2
下方投影面積		c m ²	1 . 5	7 6	6 9	6 4	6 0	7 5	6 9	6 4	6 0	7 2	6 7	6 3	5 9	7 0	6 6	6 2	5 9	5 7	
等価発光面積		c m ²	2 . 0	8 1	7 5	7 1	6 7	7 9	7 4	7 0	6 7	7 7	7 3	6 9	6 6	7 5	7 1	6 8	6 5	6 3	
取付 高さ	器具間隔最大限		2 . 5	8 3	7 9	7 5	7 2	8 2	7 8	7 4	7 1	8 0	7 6	7 3	7 0	7 8	7 5	7 2	7 0	6 7	
	横方向 (A) 縦方向 (B)		3 . 0	8 5	8 1	7 8	7 5	8 4	8 0	7 7	7 4	8 2	7 9	7 6	7 4	8 0	7 7	7 5	7 3	7 0	
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	8 8	8 5	8 2	7 9	8 6	8 4	8 1	7 9	8 4	8 2	8 0	7 8	8 2	8 0	7 8	7 7	7 4	
			5 . 0	8 9	8 7	8 4	8 2	8 8	8 6	8 3	8 2	8 6	8 4	8 2	8 0	8 4	8 2	8 0	7 9	7 7	
			7 . 0	9 1	8 9	8 7	8 5	9 0	8 8	8 6	8 5	8 7	8 6	8 5	8 3	8 5	8 4	8 3	8 2	8 0	
			1 0 . 0	9 2	9 1	8 9	8 8	9 1	9 0	8 8	8 7	8 9	8 8	8 7	8 6	8 7	8 6	8 5	8 4	8 2	

