

屋内照明器具特性	
品番 (品名)	L G D 9 4 0 2
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 5 5 4 (0) D R 1
B Z 分類	B Z 5

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 67	0 . 6	47	37	31	26	46	37	31	26	44	36	30	26	43	35	30	26	25
			0 . 63	0 . 8	56	46	40	35	54	46	40	35	52	45	39	35	50	43	38	35	33
			0 . 56	1 . 0	61	52	46	41	60	52	46	41	58	50	45	41	55	49	44	41	39
				1 . 25	66	58	52	48	65	57	52	47	62	56	51	47	60	55	50	47	45
下方投影面積		c m ²		1 . 5	70	62	57	52	68	62	56	52	66	60	55	52	63	58	54	51	49
			等価発光面積	c m ²	2 . 0	74	68	63	59	73	67	63	59	70	66	62	58	68	64	61	58
取付 高さ	器具間隔最大限			2 . 5	77	72	68	64	76	71	67	64	73	69	66	63	71	68	65	62	60
	横方向 (A) 縦方向 (B)			3 . 0	79	75	71	68	78	74	70	67	75	72	69	66	73	70	68	65	63
H m	1 . 25 H m	1 . 25 H m		4 . 0	82	78	75	72	81	77	74	72	78	75	73	71	76	74	72	70	67
				5 . 0	83	80	78	75	82	79	77	75	80	78	75	74	78	76	74	72	70
				7 . 0	85	83	81	79	84	82	80	78	82	80	79	77	80	78	77	76	73
				10 . 0	86	85	83	82	85	84	83	81	83	82	81	80	81	80	79	78	76

