

屋内照明器具特性	
品番 (品名)	L G S 1 5 0 1 N
光源	LED5000_70_375 ×1 375.0 lm
管理番号	K0157664 (0) DB 1
B Z 分類	BZ4 / 1.4 / BZ3

器具効率		100 %		反射率	天井	80 %					70 %					50 %					30 %					0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %					10 %					10 %					10 %					0 %
					照明率 (X0.01) ZCM																					
保守率		良 中 否	0.67	0.6	60	49	41	36	59	48	41	36	57	47	41	36	55	46	40	36	34					
			0.63	0.8	70	60	53	48	69	59	52	47	67	58	52	47	64	57	51	47	45					
			0.56	1.0	77	68	61	56	76	67	60	55	73	65	60	55	71	64	59	55	53					
				1.25	83	75	68	63	82	74	68	63	79	72	67	63	76	71	66	62	60					
下方投影面積		cm ²	1.5	87	80	74	69	86	79	73	69	83	77	72	68	80	75	71	67	65						
			2.0	92	86	81	77	91	85	81	77	88	83	79	76	86	82	78	75	73						
等価発光面積		cm ²	2.5	96	90	86	82	94	89	85	82	92	87	84	81	89	86	83	80	78						
			3.0	98	93	89	86	96	92	89	86	94	90	87	84	91	88	86	83	81						
H _m	1.22H _m	1.22H _m	4.0	101	97	94	91	99	96	93	90	97	94	91	89	94	92	90	88	85						
			5.0	102	99	97	94	101	98	96	94	98	96	94	92	96	94	92	91	88						
			7.0	104	102	100	98	103	101	99	97	100	98	97	96	98	96	95	94	91						
			10.0	105	104	102	101	104	103	101	100	102	100	99	98	99	98	97	96	94						

