

屋内照明器具特性	
品番 (品名)	LGS9001
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0190452 (0) DR 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		4 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束		9 6 %																						
保守率		良 中 否	0 . 6	7 7	7 0	6 5	6 2	7 6	6 9	6 5	6 1	7 4	6 8	6 4	6 1	7 2	6 7	6 3	6 1	5 9				
			0 . 6 3	8 4	7 7	7 2	6 9	8 2	7 6	7 2	6 9	8 0	7 5	7 1	6 8	7 8	7 4	7 0	6 8	6 6				
			1 . 0	8 8	8 2	7 7	7 4	8 7	8 1	7 7	7 3	8 4	7 9	7 6	7 3	8 2	7 8	7 5	7 2	7 0				
			0 . 5 6	1 . 2 5	9 1	8 6	8 2	7 8	9 0	8 5	8 1	7 8	8 8	8 3	8 0	7 7	8 5	8 2	7 9	7 6	7 4			
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 2	9 3	8 8	8 4	8 1	9 0	8 6	8 3	8 0	8 7	8 4	8 2	7 9	7 7				
等価発光面積			c m ²	2 . 0	9 7	9 3	9 0	8 7	9 6	9 2	8 9	8 6	9 3	9 0	8 7	8 5	9 0	8 8	8 5	8 4	8 1			
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 3	9 0	9 8	9 4	9 2	8 9	9 5	9 2	9 0	8 8	9 2	9 0	8 8	8 6	8 4				
	横方向 (A)		縦方向 (B)	3 . 0	1 0 1	9 7	9 5	9 2	9 9	9 6	9 4	9 2	9 6	9 4	9 2	9 0	9 3	9 1	9 0	8 8	8 5			
H m	0 . 4 2 H m	0 . 4 1 H m	4 . 0	1 0 2	1 0 0	9 8	9 6	1 0 1	9 8	9 6	9 5	9 8	9 6	9 4	9 3	9 5	9 3	9 2	9 1	8 8				
			5 . 0	1 0 3	1 0 1	9 9	9 8	1 0 2	1 0 0	9 8	9 7	9 9	9 7	9 6	9 5	9 6	9 5	9 4	9 3	8 9				
			7 . 0	1 0 4	1 0 3	1 0 2	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 7	9 6	9 5	9 5	9 1				
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 1	1 0 0	9 9	9 9	9 8	9 7	9 7	9 6	9 3				

