

屋内照明器具特性	
品番 (品名)	LRD9 2 0 0
光源	LLD3020MLCB1 ×1 715.0 l m
管理番号	K0175989 (0) DR 1
B Z 分類	BZ1

器具効率		6 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		6 7 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 5	5 1	4 8	4 6	5 5	5 1	4 8	4 6	5 4	5 0	4 8	4 6	5 3	5 0	4 8	4 6	4 5		
			0 . 6	0 . 8	5 9	5 6	5 3	5 1	5 9	5 5	5 3	5 1	5 8	5 5	5 3	5 1	5 7	5 4	5 2	5 1	5 0		
			0 . 5 6	1 . 0	6 2	5 9	5 6	5 4	6 1	5 8	5 6	5 4	6 0	5 8	5 5	5 4	5 9	5 7	5 5	5 4	5 3		
				1 . 2 5	6 4	6 1	5 9	5 7	6 3	6 1	5 9	5 7	6 2	6 0	5 8	5 7	6 1	5 9	5 8	5 6	5 5		
下方投影面積		c m ²	1 . 5	6 6	6 3	6 1	5 9	6 5	6 2	6 1	5 9	6 4	6 2	6 0	5 9	6 2	6 1	5 9	5 8	5 7			
等価発光面積			c m ²	2 . 0	6 7	6 5	6 3	6 2	6 7	6 5	6 3	6 2	6 5	6 4	6 2	6 1	6 4	6 3	6 2	6 1	5 9		
取付 高さ	器具間隔最大限		2 . 5	6 8	6 7	6 5	6 4	6 8	6 6	6 5	6 3	6 6	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 1			
	横方向 (A)		縦方向 (B)	3 . 0	6 9	6 8	6 6	6 5	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 2		
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	7 0	6 9	6 8	6 7	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 6	6 6	6 5	6 4	6 3			
			5 . 0	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 8	6 8	6 7	6 6	6 7	6 6	6 6	6 5	6 4			
			7 . 0	7 1	7 0	7 0	6 9	7 0	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 8	6 7	6 7	6 6	6 5			
			1 0 . 0	7 2	7 1	7 1	7 0	7 1	7 0	7 0	6 9	6 9	6 9	6 9	6 8	6 8	6 8	6 7	6 7	6 5			

