

屋内照明器具特性	
品番 (品名)	XAS3004L
光源	LED2700_70_640 ×1 640.0 lm
管理番号	K0170999 (0) D 1
BZ分類	BZ4/8.5/BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 9 %																					
保守率		良 中 否	0 . 6 7	0 . 6	5 8	4 7	3 9	3 4	5 6	4 6	3 9	3 4	5 3	4 4	3 8	3 3	5 0	4 2	3 6	3 2	3 0		
			0 . 6 3	0 . 8	6 8	5 7	5 0	4 5	6 6	5 6	4 9	4 4	6 2	5 4	4 8	4 3	5 9	5 2	4 6	4 2	3 9		
			0 . 5 6	1 . 0	7 4	6 5	5 8	5 2	7 2	6 3	5 7	5 2	6 8	6 1	5 5	5 1	6 4	5 8	5 3	4 9	4 6		
				1 . 2 5	8 0	7 1	6 5	6 0	7 8	7 0	6 4	5 9	7 3	6 7	6 1	5 7	6 9	6 4	5 9	5 6	5 2		
下方投影面積		c m ²	1 . 5	8 4	7 6	7 0	6 5	8 1	7 4	6 9	6 4	7 7	7 1	6 6	6 2	7 3	6 8	6 4	6 0	5 6			
等価発光面積			c m ²	2 . 0	8 9	8 2	7 7	7 2	8 6	8 0	7 5	7 1	8 2	7 7	7 3	6 9	7 7	7 3	7 0	6 7	6 2		
取付 高さ	器具間隔最大限		2 . 5	9 2	8 6	8 2	7 7	9 0	8 4	8 0	7 6	8 5	8 1	7 7	7 4	8 0	7 7	7 4	7 1	6 7			
	横方向 (A) 縦方向 (B)		3 . 0	9 4	8 9	8 5	8 1	9 2	8 7	8 3	8 0	8 7	8 3	8 0	7 7	8 2	7 9	7 7	7 4	6 9			
H m	1 . 2 5 H m	1 . 2 5 H m	4 . 0	9 7	9 3	8 9	8 6	9 4	9 1	8 7	8 5	9 0	8 7	8 4	8 1	8 5	8 3	8 0	7 8	7 3			
			5 . 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 1	8 9	8 6	8 4	8 7	8 5	8 3	8 1	7 6			
			7 . 0	1 0 0	9 8	9 6	9 3	9 8	9 6	9 4	9 2	9 3	9 1	9 0	8 8	8 9	8 7	8 6	8 4	7 9			
			1 0 . 0	1 0 2	1 0 0	9 8	9 7	1 0 0	9 8	9 6	9 5	9 5	9 3	9 2	9 1	9 0	8 9	8 8	8 7	8 1			

