

屋内照明器具特性		
品番 (品名)	L G W5 6 9 2 5 B	
光源	LDC5 L - E17 / C / D / W / 2 ×1 360.0 l m	
管理番号	K0169009 (0) DR 1	
B Z 分類	B Z 1 0	

器具効率		59 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		54 %	室指数	照明率 (X0.01)																				Z C M	
下方光束		5 %																							
保守率		良 中 否	0.63	0.6	25	19	15	12	22	16	13	10	15	12	9	7	9	7	6	4	0				
			0.6	0.8	30	24	19	16	26	20	17	14	18	14	12	10	11	9	7	6	0				
			0.56	1.0	33	27	23	20	28	24	20	17	20	17	14	12	12	10	9	8	0				
				1.25	36	31	27	23	31	27	23	20	22	19	16	15	13	11	10	9	0				
下方投影面積		c m ²	1.5	38	33	29	26	33	29	26	23	23	20	18	16	14	13	11	10	1					
等価発光面積			c m ²	2.0	41	37	33	30	36	32	29	27	25	23	21	19	15	14	13	12	1				
取付高さ	器具間隔最大限		2.5	43	39	36	33	37	34	32	29	26	24	23	21	16	15	14	13	1					
	横方向 (A) 縦方向 (B)		3.0	44	41	38	36	38	36	33	31	27	25	24	22	17	16	15	14	1					
H m	0.00 H m	0.00 H m	4.0	46	43	41	39	40	38	36	34	29	27	26	24	18	17	16	15	2					
			5.0	47	45	43	41	41	39	37	36	29	28	27	26	18	17	17	16	2					
			7.0	48	47	45	43	42	41	39	38	30	29	28	27	19	18	18	17	2					
			10.0	49	48	47	46	43	42	41	40	31	30	30	29	20	19	19	18	3					

